

SPECIFICATIONS PURSUANT TO CT6.74# - SLASH TREATMENT REQUIREMENTS
(02/2002)

DESIGNATED PURCHASER WORK
TIMBER SALE
SLASH PLAN AND SPECIFICATIONS
Umatilla National Forest Revision 08/09

| Spec Cross Ref Nos. | Work Item Identification | Map Symbol | ESTIMATED Amount of Work/Areas to be treated. |
|------------------------------|-----------------------------|---------------|---|
| #3, #4 | Machine Slash Piling | Map notes | <u>491</u> acres within designated areas |
| #1, #2 | Leave Top Attached | Map notes | <u>349</u> acres within designated areas |

CT6.74# SPECIFICATION

1. TRACTOR WHOLE TREE YARDING

Units No.: 3, 7, 9 and portions of 1, 6, 8 and 10.

Tops (limbs will be left attached) will be left attached to last log and yarded to the landing or other locations as designated by the Forest Service and piled after being severed from the attached log (pursuant to CT6.413#).

2. CABLE YARDING TOPS ATTACHED

Units No.: 2 and portions of 1, 6, and 8.

Tops (limbs will be left attached) will be left attached to last log and yarded to the landing or other locations as designated by the Forest Service and piled after being severed from the attached log (pursuant to CT6.413#).

3. LANDING SLASH

Landing Slash is required to be piled in the following Units No. 1, 2, 3, 7, 9, and portions of 6, 8 and 10.

Landing slash shall be piled with a brush blade on a Dozer or Skidder. Brush blades must be no wider than 10 feet and have teeth that are a minimum of 12 inches apart and 10 inches long.

The Purchaser shall pile all slash located within the used landing area that is greater than 1 inch in diameter and 3 feet long. Any material protruding more than 6 feet from the perimeter of the pile will be cut off and placed in the pile. Piles shall be located at least 20 feet from live or dead trees, roads, drainage ditches and streams.

Piles will not exceed 15 feet in height and 20 feet in diameter and will not be less than 4 feet in height and less than 6 feet in diameter.

As is practical, all piles shall be free of dirt and the duff layer will not be disturbed during piling operations.

4. MACHINE PILING SPECIFICATIONS

Purchaser shall machine pile slash produced by forwarder logging within designated areas as indicated on the Sale Area Map.

Slash is required to be piled in the following Units No. 4, 5, and portions of 6, 8 and 10

- a. In areas designated for machine piling, Purchaser shall use a brush blade/rake to pile slash as small as 1 inches in diameter at the large end and over 3 feet in length.
- b. Material protruding more than 6 feet from the perimeter of the pile will be cut off and placed on the pile.

- c. Piles will be located at least 20 feet from the drip line of live trees. Piles shall not be located on road surfaces or ditchlines unless approved by Forest Service.
- d. Piles will not exceed 10 feet in height and 15 feet in diameter and will not be less than 4 feet in height and less than 6 feet in diameter.
- e. Piles will be compact and free of soil. The Forest Service may approve substitution of track mounted loader for tractor with brush blade/rake. All burnable material will be removed from around the piles. This is not intended to include duff and/or needles.